


Line Interactive **Pro Series UPS**



Uninterrupted Power

Automatic emergency backup power available in the event of power failure.



Voltage Regulation

Provides regulated output for a wide range of input voltage variations.

Surge Protection

Full time protection against AC line surge, spike, noise and interference.



Modem Protection

Provides protection against lightning strikes entering the system through modem lines.

Communication Port

Optional RS232 port provides secure, automatic unattended system shutdown.



Specifications

Specifications:		Pro 612	Pro 724	Pro 1024	Pro 1224
Capacity		600VA	700VA	1000VA	1200VA
Input (Mains opn.)	AVR Window Range	150V - 265V			
	Frequency	50 Hz \pm 5%			
Output (on Batt.)	Voltage (on Batt.)	220-240 V AC rms (nom)			
	Transfer Time	3 m sec.			
	Waveform	Step Wave			
	Efficiency	> 83 %			
	Power Factor	0.6 lag to unity			
	Protection	Surge Protection	R.F.I., Spike & Surge		
	Input Fuse	Fuse protection			
	Short Circuit	Electronic Shutdown			
	Modem protection	RJ-11 jack standard	standard	standard	standard
Noise	Audible Noise	<40 dB at one meter		45 dB at one meter	
	RFI noise	<10dB at 0.2MHz		<12dB at 0.2MHz	
Communication	Serial Interface	RS 232 port optional			
Alarms / Display	Mains	Yellow LED	Green	Green	Green
	Standby	Green LED		(Common for all)	
	Back-up	Red LED with buzzer		(Common for all)	
Physical	Dimensions (HxWxD)	15x10x25 cm			
	Weight	6.8 Kg	10.5 Kg	11.5 Kg	12.5 Kg
Ambient	Temperature	0° C - 48° C			
	Humidity	< 95 % RH			



ELECTRONIC ENTERPRISES

67 DSIDC Complex, Okhla Industrial Area, Phase I, New Delhi 110020

Tel.: 41616509 & 26811774 Fax: 41018608

E-mail: elent@vsnl.com Web site: www.elent.in

An ISO 9001 certified company